




*'Weigh Better'*

3590EKR

3590EKR "ENTERPRISE": WEIGHT INDICATOR WITH TRANSPORT CASE FOR INDUSTRIAL APPLICATIONS



Multifunction high performance digital weight indicator in Rack version, complete with 4 connectors for linking the platforms, built-in rechargeable battery with charger, and case. Particularly suitable for mobile weighing applications. CE-M approvable (OIML R-76 / EN 45501).

 Freely Programmable



The best solution  
for advanced industrial  
applications

## MAIN FEATURES

- ABS transport case, with housing for the indicator and space for extra accessories.
- 3590EXP series indicator fit in a metallic rack type involucre with dimensions of 270x440mm, complete of housing for optional printer, connectors for platforms, and serial output on 9-pole connector.
- Dimensions: 325x460x170 mm. Weight: about 5 kg.
- 25-key alphanumeric waterproof keyboard.
- Highly efficient red led display with 6 digits 15mm high.
- Backlit LCD graphic 25x100mm display.
- Synoptic bar graph with 16 bright LEDs showing the active functions.
- Permanent time/date and data storage.
- Fitted with alibi memory.
- Functions available with the DINITOOLS utility:
  - Configuration, calibration, data entry and print formatting.
  - Recording and filing of all the information on PC, complete with the calibration data of each instrument.
  - Complete retrieval of the data saved for quick substitution.
  - Instrument calibration with numeric values.
- Selection of the programme language directly in the set-up.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- Up to 10.000e OIML or 3 x 3000e @ 0,3  $\mu$ V/d CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- Fitted with 4 connectors for connection to 4 platforms (up to 2 in the 3590EKR03P model, up to 1 in the 3590EKR09P model).
- Connectable with up to 16 analogue 350-Ohm (or 45 1000-Ohm) load cells.
- Connectable with the main digital load cells available on the market.
- Built-in rechargeable battery (10-hour minimum operating time, recharge in 8 hours) with fitted external 12 Vdc / 230 Vac adapter.
- All versions are fitted with attached thermal printer.

## APPLICATION SOFTWARE

- AFO1: Totalization and formula weighing
- AFO2: Pieces/quantity counting
- AFO3: Weighbridges - Input/Output vehicle
- AFO4: Statistical checking of prepackaged goods
- AFO5: Price computing and industrial labelling
- AFO8: Wheel and axle static weighing with 2 or various platforms
- AFO9: Dynamic and static axle weighing with 2 platforms

## CUSTOMISED APPLICATIONS

Thanks to our integrated development, you can create complete customised applications in autonomy:

- wizards, operator messages
- serial port management, protocols customization
- digital I/O full management
- sequential or simultaneous automations
- data entry, custom archives

Dini Argeo can offer the service of custom development programs.

## I/O SECTION

- Available on panel:
  - One RS232 serial ports, for connection to PC, on 9-pole connector.
- Available on internal side:
  - Two RS232 serial ports, for connection to printer, PC or PLC, radio module, and optional interfaces.
  - One RS232 serial port (optional RS485), for connection to repeater, remote scale, badge reader or digital load cells.
  - Fitted keyboard emulation input, for barcode/badge readers or external PC keyboard.
  - 4 optoisolated outputs (optional).
  - 2 optoisolated inputs (optional).



GRAVITATION LTD.

UNIT 2B SECTION 5 DUNSHAUGHLIN - - CO. MEATH - IRELAND

Tel. 00353469078900

Fax. 00353469078911

E-mail [info@gravitation.ie](mailto:info@gravitation.ie)

Web [www.gravitation.ie](http://www.gravitation.ie)